

2FE22

2.5" - 25 W - 89 dB - 8 Ohm



NOMINAL SPECIFICATIONS	
Nominal Diameter	66 mm (2.5 in)
Overall Diameter	88/68 mm (3.46/2.68 in)
Bolt Circle Diameter	75 mm (2.95 in)
Baffle Cutout Diameter	60.5 mm (2.38 in)
Depth	35.5 mm (1.40 in)
Flange and Gasket Thickness	6 mm (0.24 in)
Net Weight	184 g (0.4 lb)
Shipping Box (Single Carton Box - 36 units)	285 x 285 x 255 mm (11.2 x 11.2 x 10 in)
Shipping Weight (36 units)	8 kg (17.6 lb)

PART NUMBER	
Faston Terminals - 8 Ohm Version	00664410

- NOTES:**
- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
 - (2) Maximum power is defined as 3dB greater than nominal power.
 - (3) EPDM (Rubber)
 - (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
 - (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS	
Nominal Impedance	8 Ohm
Minimum Impedance	7.1 Ohm
AES Power Handling (1)	25 W
Maximum Power Handling (2)	50 W
Sensitivity (1W/1m)	89 dB
Frequency Range	125-20000 Hz
Voice Coil Diameter	19 mm (0.75 in)
Winding Material	Al
Former Material	Kapton
Winding Depth	6.8 mm (0.27 in)
Magnetic Gap Depth	3 mm (0.12 in)
Flux Density	1.65 T
Magnet	Neodymium Ring
Basket Material	Polycarbonate
Demodulation	No
Cone Surround (3)	Half Roll
NET Air Volume filled by Loudspeaker	0.030 dm ³ (0.001 ft ³)
Spider Profile	1x constant height waves

THIELE & SMALL PARAMETERS	
Fs	125 Hz
Re	6.5 Ohm
Qes	0.43
Qms	3.1
Qts	0.38
Vas	0.5 dm ³ (0.02 ft ³)
Sd	20.1 cm ² (3.12 in ²)
Xmax (4)	2.90 mm
Xdamage (5)	5.3 mm
Mms	2 g
Bl	5.2 N/A
Le	0.15 mH
Mmd	1.9 g
Cms	0.81 mm/N
Rms	0.5 kg/s
Eta Zero	0.23 %
EBP	291 Hz

