



40W

## AIRMT-85

Order No.: 01.3190

**Price upon request**

### PRODUCTINFOS

#### Air Motion Transformers

are a special type of tweeter systems which have been developed by the German physicist Oskar Heil during his research on the characteristics of the human ear. The main feature is a film-covered cone with a special folding which vibrates like an accordion when an audio signal is applied. This folding allows to accommodate a large cone area at a minimum of space. The AMTs feature a dynamic sound, an excellent transient response, a high efficiency and a low harmonic distortion.

#### High-end Air Motion Transformer tweeter, 20 W, 4 $\Omega$

- Tweeter based on the principle of Air Motion Transformer
- High-performance neodymium magnet system
- Fine, dynamic and brilliant reproduction of the high frequencies
- Folded cone made of Kapton and aluminium
- High efficiency
- For use from 2,500 Hz on
- Robust aluminium front panel

## Klang+Ton 08,09/2016

“Compact AMT with quite a low crossover frequency possible for two-way speaker systems and multi-way speaker systems of highest quality.”

## TECHNICAL SPECIFICATIONS

### AIRMT-85

Impedance (Z)	4 Ω
Frequency range	2,000-30,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	> 2,500 Hz
Power rating (RMS)	20 W
Peak music power output (MAX)	40 W
Sensitivity	92 dB/W/m
DC resistance (Re)	3.8 Ω
Magnet diameter	neodymium rods
Mounting cutout	Ø 66 mm
Mounting depth	36 mm
Mounting hole diameter	Ø 75 mm
Dimensions	Ø 85 mm x 36 mm
Outside diameter	Ø 85 mm
Width	Ø 85 mm
Depth	36 mm
Admiss. ambient temp.	0-40 °C
Weight	0.3 kg
Packing unit	1