



FGA-35

Order No.: 21.2420

Price upon request

PRODUCTINFOS

Ground isolator,

compact design, for preventing signal interference and hum loops which may occur, e.g. when connecting PC sound cards or laptops to an amplifier.

- Galvanically isolated inputs and outputs
- 2 x 3.5 mm stereo plug
- Input/output impedance: 20 kΩ
- Frequency range: 20-30,000 Hz
- THD: < 0.01%
- Transmission ratio 1:1
- Ø 24 mm x 38 mm, 32 g
- Length including connection cable: approx. 80 cm

TASTENWELT 04/2014

"The FGA-35 is a compact transmitter and ideally suited for connecting instruments (e.g. stage pianos) to an audio device without interference."



TECHNICAL SPECIFICATIONS

FGA-35

Description ground isolator Frequency range 20-30,000 Hz

 $\begin{array}{ll} \mbox{Input impedance} & 20 \ k\Omega \\ \mbox{Output impedance} & 20 \ k\Omega \\ \mbox{Transmission ratio} & 1:1 \end{array}$

THD \$<0.01%\$ Admiss. ambient temp. $$0\text{-}40\ ^{\circ}\text{C}$$

Dimensions Ø 24 mm x 38 mm

Weight 31 g

Inputs $1 \times 3.5 \text{ mm}$ stereo plug Outputs $1 \times 3.5 \text{ mm}$ stereo plug