



80 W

RBT-1000

Order No.: 10.1610

Price upon request

PRODUCTINFOS

Ribbon tweeter for PA and hi-fi, 40 W, 6 Ω

- Magnetostatic speaker with waveguide
- Tweeter system from the L-RAY/1000
- Fine and brilliant reproduction of the high range
- For use from 3,000 Hz (hi-fi) or 4,000 Hz (PA) on via 18 dB filter
- Diecast aluminium horn front attachment, neodymium magnet
- Vertical or horizontal mounting possible due to square front panel

TECHNICAL SPECIFICATIONS

RBT-1000

| | |
|---|--------------|
| Impedance (Z) | 6 Ω |
| Frequency range | fx-22,000 Hz |
| Resonant frequency (fs) | 1.6 kHz |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | > 2,500 Hz |

RBT-1000

| | |
|-------------------------------|-----------------------|
| Power rating (RMS) | 40 W |
| Peak music power output (MAX) | 80 W |
| Sensitivity | 96 dB/W/m |
| Magnet diameter | magnetostatic speaker |
| Mounting cutout | 94 x 94 mm |
| Mounting depth | 24 mm |
| Hole spacing X-axis | 87 mm |
| Hole spacing Y-axis | 87 mm |
| Dimensions | 104 x 104 x 24 mm |
| Width | 104 mm |
| Height | 104 mm |
| Depth | 24 mm |
| Admiss. ambient temp. | 0-40 °C |
| Weight | 0.24 kg |
| Packing unit | 1 |