



60W

RBT-95

Order No.: 10.2250

Price upon request

PRODUCTINFOS

Ribbon tweeter, 30 W, 8 Ω

- Magnetostatic speakers of a high efficiency
- Perfectly fine dynamic reproduction of the high range and the brilliance frequency range
- Power capability of the system can considerably be increased by voltage dividers and maybe higher crossover frequencies (level attenuations which take tweeters to the level of normal hi-fi systems)
- Very light sound of low distortion which particularly improves the stereophony in applications from 5 kHz on
- By adding a super tweeter above 8-10 kHz, e.g. even high-quality full range systems can be further improved

TECHNICAL SPECIFICATIONS

RBT-95

Impedance (Z)	8 Ω
Frequency range	fx-22,000 Hz
Resonant frequency (fs)	4,500 Hz

RBT-95

Rec. crossov. frequ. (fmax.) (12 dB/oct.)	5,000 Hz
Power rating (RMS)	30 W
Peak music power output (MAX)	60 W
Sensitivity	98 dB/W/m
Magnet diameter	magnetostatic speaker
Mounting cutout	80 x 45 mm
Mounting depth	17 mm
Hole spacing X-axis	56 mm
Hole spacing Y-axis	56 mm
Dimensions	Ø 95 x 17 mm
Outside diameter	Ø 95 mm
Width	Ø 95 mm
Depth	17 mm
Admiss. ambient temp.	0-40 °C
Weight	0.11 kg
Packing unit	1