



## SOUND-100SUB

Order No.: 25.0730

**Price upon request**

### PRODUCTINFOS

#### **With the 2-way Active Systems and the Subwoofers of the SOUND Series,**

efficient speakers with a powerful sound are available in different sizes and with different features. They are all integrated into high-quality bass-reflex MDF cabinets and feature speakers with magnetic shielding. The speaker systems are ideally suited as active hi-fi speaker systems, high-end PC speakers and for small PA applications requiring a powerful sound, e.g. media presentations.

#### **Active subwoofer system, 120 W**

- Active subwoofer for adding to the active SOUND speaker systems, but also to any other compact speaker for hi-fi or home cinema applications and home recordings
- Amplifier features variable input sensitivity, a phase switch, an automatic switch-on system which can additionally be activated as well as an adjustable crossover frequency (50-150 Hz)
- High-quality bass-reflex MDF cabinet (black wood veneer look)
- 25 cm (10") bass speaker
- Volume control for the subwoofer
- Inputs via 1 x RCA L/R, RCA LFE or screw terminals for high-level L/R
- Additional outputs for mid-high range speakers, thus well-suited for connection to already existing speaker cables

## TECHNICAL SPECIFICATIONS

### SOUND-100SUB

Active/passive	active
Power rating (RMS)	120 W
Frequency range	35-100 Hz
Input signal	150 mV/24 k $\Omega$ (RCA L/R)
	55 mV/16 k $\Omega$ (RCA mono)
	2.3 V/440 $\Omega$ (high IN)
Bass speaker	25 cm (10") bass speaker
Number of speakers	1
Speaker size	25 cm (10")
Sensitivity	88 dB/W/m
Max. rated SPL	108 dB
Housing material	wood
Colour	black
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/240 VA
Dimensions	330 x 360 x 360 mm
Width	330 mm
Height	360 mm
Depth	360 mm
Weight	13 kg
Inputs	1 x RCA (L/R), unbal., IN
	1 x RCA (mono), unbal., IN
	1 x screw terminal (stereo), high-level IN
Outputs	1 x screw terminals (stereo), high-level out