



SOUND-4BT/WS

Order No.: 25.7060

Price upon request

PRODUCTINFOS

Active 2-way stereo speaker system,

with Bluetooth receiver, 2 x 30 W.

- Set consists of one active and one passive bass-reflex speaker system. Connection of the passive system to the active system via spring-loaded speaker terminals
- Bluetooth receiver V4.0 with APTX
- Active speaker system with integrated 2-channel class D amplifier
- Stereo RCA and 3.5 mm jack input, optical digital input (Toslink), mono sub out via RCA jack
- Supplied with remote control
- 10 cm (4") bass speaker and 25 mm (1") dome tweeter
- Excellent sound characteristics with linear adjustment
- High-gloss lacquered MDF wooden cabinet of high quality

TECHNICAL SPECIFICATIONS

SOUND-4BT/WS

Active/passive	active
Power rating (RMS)	2 x 30 W
Frequency range	45-20,000 Hz
Input signal	Bluetooth 500 mV/10 kΩ
System	2-way
Bass speaker	10 cm (4") bass speaker
Tweeter	25 mm dome tweeter
Number of speakers	2
Speaker size	10 cm (4")
Sensitivity	85 dB/W/m (each speaker system)
Max. rated SPL	98 dB (each speaker system)
Housing material	MDF
Colour	white
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/170 VA
Dimensions	140 x 215 x 170 mm
Width	140 mm
Height	215 mm
Depth	170 mm
Weight	5.2 kg (pair) 1 x RCA L/R
Inputs	1 x 3.5 mm stereo jack 1 x Toslink, optical digital input
Other features	spring-load. speaker term. for passive sp. system Bluetooth 4.0, APTX, remote control