



SP-150

Order No.: 0100320

PRODUCTINFOS

Hi-fi bass midrange speaker, 30 W, 8 Ω

- White polypropylene cone
- Basket with plastic trim ring

TECHNICAL SPECIFICATIONS

SP-150

Impedance (Z)	8 Ω
Frequency range	f3-4,000 Hz
Resonant frequency (fs)	35 Hz
Power rating (RMS)	30 W
Peak music power output (MAX)	60 W
SPL	90 dB/W/m
Suspension compl. (Cms)	1.56 mm/N
Moving mass (Mms)	10.4 g

SP-150

Mech. Q factor (Qms)	2.83
Electr. Q factor (Qes)	0.61
Total Q factor (Qts)	0.5
Equivalent volume (Vas)	35 l
DC resistance (Re)	6.5 Ω
Force factor (BxL)	7.50 Tm
Voice coil induct. (Le)	0.45 mH
Voice coil diameter	\varnothing 25.5 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	\pm 2.5 mm
Eff. cone area (Sd)	127 cm ²
Magnet weight	380 g
Magnet diameter	\varnothing 100 mm
Mounting cutout	\varnothing 145 mm
Mounting depth	65 mm
Mounting hole diameter	\varnothing 156 mm
Hole spacing X-axis	110 mm
Hole spacing Y-axis	110 mm
Dimensions	\varnothing 170 mm x 75 mm
Outside diameter	\varnothing 170 mm
Width	\varnothing 170 mm
Depth	75 mm
Colour	black/white
Admiss. ambient temp.	0-40 °C
Weight	1.215 kg
Packing unit	1
Type of speaker	6"
Packing dimensions (W x H x L)	0.18 x 0.09 x 0.18 m
Gross weight	1.29 kg
Net weight	1.215 kg