



SP-252E

Order No.: 10.3990

Price upon request

PRODUCTINFOS

Hi-fi bass-midrange speaker, 75 W, 4 Ω

- Multi-purpose speaker
- Foam surround
- Replacement speaker for closed cabinets

TECHNICAL SPECIFICATIONS

SP-252E

Impedance (Z)	4 Ω
Frequency range	f3-6,000 Hz
Resonant frequency (fs)	42 Hz
Power rating (RMS)	75 W
Peak music power output (MAX)	150 W
Sensitivity	94 dB/W/m
Suspension compl. (Cms)	0.33 mm/N

SP-252E

Moving mass (Mms)	43 g
Mech. Q factor (Qms)	3.13
Electr. Q factor (Qes)	0.60
Total Q factor (Qts)	0.50
Equivalent volume (Vas)	57 l
DC resistance (Re)	3.75 Ω
Force factor (BxL)	8.50 Tm
Voice coil induct. (Le)	1.1 mH
Voice coil diameter	\varnothing 35.5 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	\pm 4 mm
Eff. cone area (Sd)	353 cm ²
Magnet weight	960 g
Magnet diameter	\varnothing 125 mm
Mounting cutout	\varnothing 232 mm
Mounting depth	110 mm
Mounting hole diameter	\varnothing 255 mm
Dimensions	\varnothing 255 mm x 110 mm
Outside diameter	\varnothing 255 mm
Width	255 mm
Depth	110 mm
Admiss. ambient temp.	0-40 °C
Weight	2.3 kg
Packing unit	1
Type of speaker	10"