



3D View



Principal Diagram



1. Voltage: 1.5V-250VAC/DC
2. Current: 3mA~5A
3. LED Voltage: 3V~220VAC/DC
4. LED Current: 3mA~20mA
5. LED Color: Blue
6. Switch Function: Latching or Momentary
7. Operating Temperature: -30°C~+80°C
8. Operating Force: Appr. 2.5~3N
9. Connection Mode: 1NO 1NC
10. Installation Mode: Solder
11. Panel Mount Size: 16mm
12. IP Class: IP 67
13. Protection Class: IK 10
14. LED Life: 40,000 hours
15. Electrical Life: 50,000 Cycles
16. Mechanical Life: 250,000 Cycles
17. Contact Resistance: ≤50mΩ
18. Insulation Resistance: ≥1000mΩ
19. Dielectric Strength: 1900VACmin

© Parts Express®




parts-express.com

RevNo	Revision note	Date	Signature	Checked	Approved
1:					
2:					
3:					
4:					

Designed by	Checked by	Approved by	Date	Scale
AH	MG	MP	2/2021	None

Part: 060-958

Name: SPDT Latching 16mm Stainless Steel Tamper/Waterproof Raised Push Button Switch with Blue Ring



Edition	Unit mm	Sheet 1 of 1
A		