


- Corundum Dome
- Large Rear Chamber
- Low Resonance
- Ferrite Magnet with Heatsink
- High Power and Thermal Handling




SPECIFICATIONS

Transducer Size	32	mm	
Impedance	8	Ω	
Frequency Range ¹	900 - 20000	Hz	
Sensitivity ² (2.83V 1W @ 1m)	88.1 88.1	dB	
Power Rating (IEC 268-5)	25	W	
Voice Coil Size	32.5	mm	
Air Gap Winding Height	H_{ag} H_{vc}	4.5 2.81	mm
Net Weight	1.33	kg	

PARAMETERS ³

Eff. Piston Area	S_d	12	cm ²
DC Resistance	R_e	6.8	Ω
Minimum Impedance	Z_{min}	7.6	Ω
Inductance	L_e	0.034	mH
Resonance Frequency ⁴	F_s	630	Hz
Mechanical Q Factor	Q_{ms}	1.73	-
Electrical Q Factor	Q_{es}	0.621	-
Total Q Factor	Q_{ts}	0.46	-
Moving Mass	M_{ms}	0.484	g
Compliance	C_{ms}	130	$\mu\text{m}/\text{N}$
Equivalent Volume	V_{as}	0.027	L
Motor Force Factor	Bl	4.59	Tm
Motor Efficiency	β	3.09	$(Bl)^2 / R_e$
Linear Excursion ⁵	X_{max}	1.78	mm



Details on this spec sheet are for reference only and should not be used for setting production limits. Specifications and product cosmetics are subject to change without notice. Peerless is a registered trademark of Tympany Enterprises. All measurements conducted in test lab at 25°C ±10°C, 50%RH ±10%. ¹ Specified by Engineering as linear working range of transducer. ² Measured at 2.83V at 1m and normalized to 1W with respect to nominal impedance. ³ Measured in Free Air without preconditioning, therefore subject to some deviation. ⁴ Impedance and F_s value measured under different conditions. ⁵ Equal/Overhung: $(H_{vc} - H_{ag})/2 + H_{ag}/3$. Underhung: $(H_{ag} - H_{vc})/2 + H_{vc}/3$. ⁶ Mechanically limited excursion (e.g. bottoming, spider crash).