



XTREME SERIES

Xtreme Audio Performance
at an Unbeatable Price!

XT32-8 SPECIFICATIONS



- > Xtreme Wide Frequency Response
- > Xtreme Precise and Powerful
- > Xtreme Low Distortion
- > Xtreme Reliable
- > Designed in Germany

XT32-8 SPECIFICATIONS

Electrical and Mechanical Properties

Rms Noise Test [W]	20
Long-term Max Power [W]	40
Frequency Range [Hz]	35Hz – 17kHz
Nominal Impedance [Ohm]	8
DC Resistance [Ohm]	7.22
Le [mH]	0.21
Kms [N/mm]	8.18
Cms [mm/N]	0.12
Bl [N/A]	5.54
Linear Xmax [mm]	± 1.6
Mechanical Xmax [mm]	± 3.5

Position Related Properties	Magnet	Coil
Fs [Hz]	39.3	305
Mms [g]	131	2.22
Rms [Kg/s]	1.58	0.20
Qts	5.39	1.23
Qms	20.8	25.7
Qes	7.27	1.29

Physical Properties

Total Weight [g]	133
Outer Diameter [mm]	54.5
Maximum Length [mm]	72.5
Total Height [mm]	24.8
Voice Coil Diameter [mm]	32
Voice Coil Layers	2
Voice Coil Mount Diameter [mm]	36

